

DaimlerChrysler AG
Stuttgart

Patent Claims

1. Joining connection between a circumferentially closed
5 hollow profile (1) and an add-on part (2) which is
provided with a passage opening (5), consists of a
material of lower yield strength than the material of the
hollow profile (1) and, on the inside (7) of the passage
opening (5), has a recess (10) which is spaced away from
10 the end sides (8, 9) of the add-on part (2), the add-on
part (2) being slid with its passage opening (5) onto the
hollow profile (1) and being jammed to the latter in this
sliding-fit position by a local expansion of the hollow
profile (1), said expansion being formed by means of
15 internal high-pressure deformation at the location of the
recess (10).

2. Joining connection according to Claim 1, characterized
in that the recess (10) is an annular freely turned
recess.

20 3. Joining connection according to Claim 1, characterized
in that the hollow profile (1) consists of a ductile
steel material, preferably of St 37 or St 52, and the
add-on part (2) consists of a casting material, of a die
casting or injection moulding, preferably of ZnAl4Cu1, or
25 of a lower-strength steel or of a light metal material.

4. Joining connection according to Claim 1, characterized
in that the recess (10) is of curved design with a
shallow rise from its base (15) as far as its edges (16).

5. Joining connection according to Claim 1, characterized

in that the expanded point of the hollow profile (1) bears in an exact manner against the walls (14) of the recess (10).

6. Method for producing a joining connection between a
5 circumferentially closed hollow profile (1) and an add-on
part (2) which is provided with a passage opening (5) and
consists of a material of lower yield strength than the
material of the hollow profile (1), a recess (10) which
10 is spaced away from the end sides (8, 9) of the add-on
part (2) being formed on the inside (7) of the passage
opening (5), after which the add-on part (2) is slid with
its passage opening (5) onto the hollow profile (1), and
subsequently the hollow profile (1), in the sliding-fit
15 position reached, is expanded locally into the recess
(10), by a fluidic internal high pressure by means of an
expansion lance inserted into the hollow profile (1), in
such a manner that the hollow profile (1) is jammed
immovably to the add-on part (2).

7. Method according to Claim 6, characterized in that the
20 recess (10) is of curved design with a shallow rise from
its base (15) as far as its edges (16), and in that the
hollow profile (1) is expanded until it bears completely
against the recess walls (14).

8. Method according to Claim 6, characterized in that the
25 add-on part (2) is cast as a cast part having a discarded
core, the recess (10) being cast at the same time.

9. Method according to Claim 6, characterized in that the
add-on part (2) is injection moulded or die cast and the
recess (10) is subsequently freely turned.

30 10. Method according to Claim 6, characterized in that
the add-on part (2) is formed, in particular forged, from

a low-strength steel, and in that the recess (10) is then engraved, turned or milled out.

11. Steering column of motor vehicles having a casing tube which surrounds a steering spindle and forms a hollow profile, and a holder, constituting an add-on part, for example for a steering column switch, the holder being joined onto the casing tube, characterized in that the holder (2), which consists of a material of lower yield strength than the material of the casing tube (1), has a circumferentially closed passage opening (5) and is slid with the latter onto the casing tube (1), the passage opening (5) having, on the inside (7), at least one recess (10) which is spaced away from the end sides (8, 9) of the holder (2), which end sides lie transversely with respect to the longitudinal direction of the casing tube (1), and in that the casing tube (1) has a locking element which, in the sliding-fit position of the holder (2), is shaped radially from the wall of the said holder locally at the location of the recess (10) by a fluidic internal high pressure and is jammed in the recess (10) as a consequence of its shape, forming a nonreleasable joining connection between the holder (2) and casing tube (1).

12. Steering column according to Claim 11, characterized in that the locking element bears over the entire surface against the recess walls (14).

13. Steering column according to Claim 11, characterized in that the recess (10) is formed by an annular groove and the locking element is formed by an annular bead (17).

14. Steering column according to Claim 11, characterized in that the casing tube (1) consists of a ductile steel

material, preferably of St 37 or St 52, and the holder (2) consists of a casting material or of an injection moulding or die casting, preferably of ZnAl4Cu1, or of a low-strength steel or of a light metal material.

- 5 15. Steering column according to Claim 11, characterized in that the recess (10) is of curved design with a shallow rise from its base (15) as far as its edges (16).